

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 55-109155

(43)Date of publication of application : 22.08.1980

(51)Int.Cl.

H02K 13/00
H01R 39/26

(21)Application number : 54-014857

(71)Applicant : MATSUSHITA ELECTRIC WORKS LTD

(22)Date of filing : 09.02.1979


(72)Inventor : YOSHIOKA KATSUHIRO
TAKAGI YASUYUKI

(54) CARBON BRUSH FOR MOTOR

(57)Abstract:

PURPOSE: To prevent abnormal noises, abrasion, and the like by forming V-shaped protruded portions at the contact points of a carbon brush and a commutator in order to make point contact, thereby the contact portions are suitably fit each other.

CONSTITUTION: A tubular commutator 2 is fixed to a motor shaft 1, and a carbon brush 4 is resiliently contacted by a plate spring 3. Two V-shaped protruded portions are formed at both sides of the edge of the carbon brush 4, and the tips of the protruded portions are slidingly contacted with a tubular commutator 2. In this constitution, the carbon brush and the commutator are point-contacted, inclining and rolling of the brush are reduced, and stable contact conditions can be obtained.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]


[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]


[Date of extinction of right]

發明 103155(3)


第 4 圖




第 2 圖




第 1 圖




第 5 圖




第 6 圖



第 3 圖



第 7 圖



第 8 圖

